

Data Logger for Cloud Storage

TR-7wf Series



and Infrared / USB Data Loggers
TR-7Ui Series



Easy-to-Use Data Loggers for Wide Variety of Measurements

Simultaneous Multi-Channel Measurement with One Device



TR-73U

- Barometric Pressure
- Temperature • Humidity



TR-74Ui / 74Ui-H

- Illuminance • UV Intensity
- Temperature • Humidity



TR-76Ui / 76Ui-H

- CO2 • Temperature
- Humidity

Start Recording upon USB connection



Data Analysis using Graph Tools



Graph Display on a Data Collector



Graph View



Simple startup upon connection to PC

- Monitor multiple channels of data in trend graph

Transmit Recorded Data to PC via USB Connection

Easy USB connection, for one device or for as many devices as your PC has ports for, makes it easy to gather current readings from the connected device(s) to your computer and view those readings in the computer display.

Data Loggers for a Variety of Measurements

The TR-7Ui series data loggers are designed to simultaneously measure and record a variety of measurements. In addition to temperature and humidity, TR-73U can record barometric pressure, TR-74Ui models take care of illuminance and UV intensity, and TR-76Ui models log CO2 concentration.

Get Temperature and Humidity in a Wider Range with Greater Accuracy


H-type models (model names which include "H") come with our high precision temperature/humidity sensor. Features include a humidity measurement accuracy of $\pm 2.5\%$, as well as the wide range measurement of temperature from -30 to 80 °C and humidity from 0 to 99%RH.


Large Logging Capacity: 8000 Data Sets


One data set consists of readings for all channels in that type of unit. If set at a recording interval of 60 minutes, it gives the user one year's worth of measurements.


Application Examples

- For managing temperature and humidity in hospitals, museums, and temperature controlled warehouses
- Managing CO2, temperature and humidity in schools: from kindergartens to universities
- For research studies on photosynthesis and growth of plants
- Measuring the degree of air tightness in packaging during transportation
- For management of illuminosity and UV light (to prevent deterioration of exhibits) in art museums and other exhibit forums



Temperature (2ch)	Temperature / Humidity	
		
		<p>High Precision Type</p> 
TR-71wf	TR-72wf	TR-72wf-H
Measurement Range Temperature: -40 to 110 °C (Supplied Sensor) -60 to 110 °C (Optional Sensor) Fluoropolymer Coated Type) Temperature Sensors (TR-0106 x 2) Included	Measurement Range Temperature: 0 to 55 °C Humidity: 10 to 95 %RH Temperature/Humidity Sensor (THA-3001) Included	Measurement Range Temperature: -30 to 80 °C Humidity: 0 to 99 %RH High Precision Temperature/Humidity Sensor (HHA-3151) Included

Temp/Humidity/Barometric-Pressure	Illuminance / UV Intensity / Temperature / Humidity	
		
		<p>High Precision Type</p> 
TR-73U	TR-74Ui	TR-74Ui-H
Measurement Range Temperature: -10 to 60 °C (Internal Sensor) 0 to 50 °C (Supplied Sensor) -40 to 110 °C (Optional Sensor) Humidity: 10 to 95 %RH (Supplied Sensor) Barometric Pressure: 750 to 1100 hPa (Internal Sensor) Temperature/Humidity Sensor (TR-3100) Included	Measurement Range Illuminance: 0 lx to 130 klx UV Intensity: 0 to 30 mW/cm ² Temperature: 0 to 50 °C Humidity: 10 to 95 %RH Display Range of Cumulative Measurement: Illuminance 0 lxh to 90 Mixh UV Intensity 0 mW to 62 W/cm ² h Temperature/Humidity Sensor (THA-3151) and Illuminance UV Sensor (ISA-3151) Included	Measurement Range Illuminance: 0 lx to 130 klx UV Intensity: 0 to 30 mW/cm ² Temperature: -30 to 80 °C Humidity: 0 to 99 %RH Display Range of Cumulative Measurement: Illuminance 0 lxh to 90 Mixh UV Intensity 0 mW to 62 W/cm ² h High Precision Temperature/Humidity Sensor (HHA-3151) and Illuminance UV Sensor (ISA-3151) Included

CO2 / Temperature / Humidity	Data Collector	
		
	<p>High Precision Type</p> 	<p>Infrared Communication Type</p> 
TR-76Ui	TR-76Ui-H	TR-57DCi
Measurement Range CO2: 0 to 9,999 ppm Temperature: 0 to 50 °C Humidity: 10 to 95 %RH Temperature/Humidity Sensor (THA-3001) Included	Measurement Range CO2: 0 to 9,999 ppm Temperature: -30 to 80 °C Humidity: 0 to 99 %RH High Precision Temperature/Humidity Sensor (HHA-3151) Included	Compatible Devices Infrared Communication: TR-74Ui / 76Ui (Including H Type) Cable Communication: TR-73U / 74Ui / 76Ui (Including H Type) Storage Capacity: Up to 256,000 readings When downloading units at full logging capacity: 10 units of TR-73U, TR-76Ui 7 units of TR-74Ui • When downloading units at non-full logging capacity, it can store and manage up to 250 downloading sessions. • Not compatible with TR-7wf series loggers.


Temperature Sensors for TR-71wf / 73U

Measurement Range: -40 to 110°C, Sensor Temperature Durability: -50 to 115 °C, Accuracy: Avg. ±0.3°C [-20 to 80°C], Avg. ±0.5°C [-40 to -20 °C / 80 to 110 °C]

Materials: ① Thermistor ② TPE resin-shielded sensor ③ TPE resin-shielded wire ④ M3Screw Hole ⑤ Compaction Tube ⑥ Stainless Pipe (SUS304) ⑦ Stainless Pipe (SUS316) *Only stainless section is water resistant.


TR-0106

TPE Resin-Shielded Sensor
Response Time (90%):
Approx. 190 sec. (in air)




TR-0306

Stainless Protection Sensor
Response Time (90%):
Approx. 11 sec. (in agitated water)




TR-0506

Stainless Protection Sensor
Response Time (90%):
Approx. 10 sec. (in agitated water)




TR-0206

Screw-down Sensor
Response Time (90%):
Approx. 210 sec. (in air)




TR-0406

Stainless Protection Sensor
Response Time (90%):
Approx. 15 sec. (in agitated water)



TR-0706

Stainless Protection Sensor
Response Time (90%):
Approx. 11 sec. (in agitated water)




Temperature Sensors for TR-71wf (Fluoropolymer Coated Type)

Measurement Range: -60 to 155°C, Sensor Temperature Durability: -70 to 180°C, Accuracy: Avg. ±0.5°C [-40 to 80°C], Avg. ±1.0°C [-60 to -40°C / 80 to 100°C], Avg. ±2.0°C [100 to 155°C]

Materials: ① Thermistor ② Stainless Pipe (SUS316) ③ Fluoropolymer-Coated Compaction Tube ④ Fluoropolymer-Coated Electrical Wire


TR-1106

Fluoropolymer Coated Sensor
Response Time (90%):
Approx. 80 sec. (in air)
Approx. 7 sec. (in agitated water)



TR-1320

Stainless Protection Sensor
Response Time (90%):
Approx. 90 sec. (in air)
Approx. 3 sec. (in agitated water)



TR-1220

Stainless Protection Sensor
Response Time (90%):
Approx. 150 sec. (in air)
Approx. 7 sec. (in agitated water)




Temperature / Humidity Sensors for TR-72wf / 74Ui / 76Ui

Materials: ① Temp/Humidity Sensor ② Polypropylene Resin ③ Polycarbonate ④ Vinyl Chloride Coated Electrical Wire


THA-3001

Measurement Range: (*1)
Temperature: 0 to 55 °C
Humidity: 10 to 95 %RH (no condensation)
Accuracy:
Temperature: ±0.5 °C
Humidity: ±5 %RH [at 25 °C and 50 %RH]
Response Time (90%): Approx. 7 min.




HTA-3151 : High Precision Type

Measurement Range: (*1)
Temperature: -30 to 80 °C
Humidity: 0 to 99 %RH
Accuracy:
Temperature: ±0.3 °C [0 to 50 °C], ±0.5 °C [at all other temperatures] 10
Humidity: ±2.5%RH [at 25°C, 10 to 85 %RH], ±4%RH [at 25°C, 0 to 10 %RH or 85 to 99 %RH] At temperatures other than 25 °C and ≥ 0 °C, add ±0.1%RH per degree of difference from 25. Humidity Hysteresis: ±1.5 %RH or lower (*2)
Response Time (90%):
Temperature: Approx. 7 min.
Humidity: Approx. 20 sec.
Long Term Stability: ±1 %RH/yr, ±0.1 °C/yr (under normal operational conditions) (*1)



THA-3151

Measurement Range: (*1)
Temperature: 0 to 55 °C
Humidity: 10 to 95 %RH (no condensation)
Accuracy:
Temperature: ±0.5 °C
Humidity: ±5%RH [at 25 °C and 50 %RH]
Response Time (90%): Approx. 7 min.



*1: Do not expose to condensation, dampness, corrosive gases, or organic solvents (or insecticides for High Precision Temperature / Humidity Sensors).
*2: When used in environments where temperature and humidity are over the values of 50°C/75%, 60 °C 50%, 70 °C 35%, and 80 °C 25%, sensor hysteresis may fluctuate by values greater than ±1.5 %RH. Under certain circumstances, it may take some time to return to normal measurement capability.


Temperature / Humidity Sensors for TR-73U

Measurement Range: Temperature 0 to 50 °C, Humidity 10 to 95 %RH
Accuracy: Temperature Avg. ± 0.3°C [0 to 50 °C], Humidity ±5%RH [at 25 °C and 50 %RH]

Materials: ① Temperature/Humidity Sensor ② Polypropylene Resin ③ Vinyl Coated Electrical Wire


TR-3100

Response Time (90%):
About 7 min.



TR-3110


Response Time (90%):
About 7 min.



Illuminance / UV Sensor for TR-74Ui

ISA-3151


Measurement Range:
Illuminance: 0 lx to 130 klx
UV Intensity: 0 to 30 mW/cm²
Accuracy: (*1)
Illuminance: ±5 % [10 lx to 100 klx at 25 °C, 50 % RH]
UV Intensity: ±5% [0.1 to 30 mW/cm² at 25 °C, 50 %RH]
Relative Spectral Response:
Illuminance: Approximated to the CIE standard response function V (λ).
UV Intensity: 260 to 400 nm (UVA / UVB)
Operating Environment: (*2)
Temperature: -10 to 60 °C
Humidity: 90 %RH or less (no condensation)
Materials: ① Polycarbonate ② Glass ③ Vinyl Coated Electrical Wire
*1: Compared to the value measured by the T&D standard sensor for calibration under our calibration light source.
*2: Do not expose to condensation, dampness, corrosive gases, or organic solvents.



Data Collector for TR-73U / 74Ui / 76Ui

TR-57DCi


Accessories:
Software CD-ROM,
USB Communication cable (US-15C),
AAA Alkaline Battery x2,
Serial Communication Cable (TR-6C10)



Wall Attachment

TR-07K2

Accessories:
Lock Screw x2,
Double-sided adhesive tape
Compatible Unit:
TR-71wf / 72wf / 73U / 74Ui (Including H Type)
Materials: Polycarbonate



Note:
- Cracking may occur if polycarbonate is exposed to strong impact at temperatures of -30 °C or lower.

AT-76K1

Accessories:
Lock Screw x 2,
Double-sided adhesive tape
Compatible Unit: TR-76Ui (Including H Type)
Materials: Aluminum



Software Set for TR-71wf / 72wf / 72wf-H

SO-15C1

Contents:
Software CD-ROM,
USB Communication cable (US-15C)




Sensor Extension Cable

Materials: ① Vinyl Coated Electrical Wire

TR-1C30

Temperature Durability:
-25 to 60 °C




Compatible Sensors:
Temperature / Humidity Sensors (THA-3001, THA-3151, HHA-3151) (*1)
Illuminance / UV Sensor (ISA-3151) (*1)
Temperature Sensors (TR-1106, TR-1220, TR-1320, TR-0106, TR-0206, TR-0306, TR-0406, TR-0506, TR-0706) (*2)

*1: Possible to use up to three cables per sensor.
*2: Only one cable per sensor. Using an extension cable with the TR-73U may lead to measurement errors of +0.3 °C at room temperature, and +0.5 °C at -50 °C.

TR-5C10


Temperature Durability:
-25 to 60 °C
Compatible Sensors:
Temperature / Humidity Sensor
TR-3100 (*3)



*3: Only one cable per sensor.

Communication Cable

US-15C : USB Communication Cable




TR-6C10 : Serial Communication Cable

For communication between
TR-57DCi and TR-73U / 74Ui
/ 76Ui



TR-07C : Serial Communication Cable

Connector Type:
Specialized Connector D-sub
9 pin
For communication between
PC and TR-73U / 74Ui /
76Ui



Specifications

	TR-74Ui		TR-74Ui-H	
	THA-3151		HHA-3151 (High-Precision Type)	
Temperature / Humidity Sensor (External)	Thermistor	Polymer Resistance	Platinum Resistance	Electrostatic Capacitance
Measurement Channels	Temperature 1ch	Humidity 1ch	Temperature 1ch	Humidity 1ch
Measurement Units	°C, °F	%RH	°C, °F	%RH
Measurement Range	0 to 55 °C	10 to 95 %RH	-30 to 80 °C	0 to 99 %RH
Accuracy	±0.5 °C	±5 %RH [at 25 °C, 50 %RH]	±0.3°C [0 to 50 °C] ±0.5°C [all other temperatures]	±2.5 %RH [at 25 °C, 10 to 85 %RH] ±4.0 %RH [at 25 °C, 0 to 10 % or 85 to 99 %RH] At temperatures other than 25 °C and ≥ 0 °C, add ±0.1 %RH per degree of difference from 25. Humidity Hysteresis: ±1.5 %RH or lower (*)
Measurement Resolution	0.1 °C		0.1 °C	
Responsiveness	Response Time (90%): Approx. 7 min.		Response Time (90%): Approx. 7 min.	Response Time (90%): Approx. 20 sec.
Illuminance / UV Sensor (External)	ISA-3151			
Measurement Channels	Illuminance: 1ch UV Intensity: 1ch			
Measurement Units	Illuminance: lx, klx UV Intensity: mW/cm ²			
Measurement Range	Illuminance: 0 lx to 130 klx UV Intensity: 0 to 30 mW/cm ²			
Units of Cumulative Measurement	Cumulative Illuminance: lxh, klxh, Mlxh Cumulative amount of UV Light: mW/cm ² h, W/cm ² h			
Display Range of Cumulative Measurement	Illuminance: 0 lxh to 90 Mlxh UV Intensity: 0 mW to 62 W/cm ² h			
Accuracy	Illuminance: 10 lx to 100 klx: ±5 % [at 25 °C, 50 %RH] UV Intensity: 0.1 to 30 mW/cm ² : ±5 % [at 25 °C, 50 %RH] (*)			
Relative Spectral Response	Illuminance: Approximated to the CIE standard response function V (λ) UV Intensity: 260 to 400 nm (UVA / UVB)			
Measurement Resolution	Illuminance: Minimum of 0.01 lx UV Intensity: Minimum of 0.001 mW/cm ²			
Response Time (90%)	3 sec. (at recording interval of 1 sec.) 6 sec. (at other intervals)			
Logging Capacity	8,000 data sets (One data set consists of readings for all channels in that type of unit.)			
Recording Interval	Select from 15 choices: 1, 2, 5, 10, 15, 20, 30 sec. or 1, 2, 5, 10, 15, 20, 30, 60 min.			
Recording Mode	Endless (Overwrite oldest data when capacity is full) or One Time (Stop recording when capacity is full)			
LCD Display Items	Measurements, Battery Life Warning, etc. - Measurements: Illuminance / UV Intensity / Temperature / Humidity / Cumulative Illuminance / Cumulative amount of UV Light - Display Pattern: Alternating or Fixed display - Display Digits: Up to 4 digits			
Communication Interfaces	USB Communication, Serial Communication (RS-232C) (*3), Infrared Communication (IrPHY 1.2 low power)			
Power	AA Alkaline Battery (LR6) x 1			
Battery Life (*4)	Approx. 6 months			
Dimensions	H 55 mm x W 78 mm x D 18 mm			
Weight	Approx. 62 g (including battery, excluding sensor)			
Operating Environment	Temperature: -10 to 60 °C Humidity: 90 %RH or less (no condensation)			
Accessories	AA alkaline battery (LR6), USB Communication Cable (US-15C), Illuminance/UV Sensor (ISA-3151), Temperature/Humidity Sensor (THA-3151 or HHA-3151), Software (CD-ROM), User's Manual Set (Warranty Included)			
Software Compatible OS (*5)	Microsoft Windows 8 32/64 bit (*5) Microsoft Windows 7 32/64 bit Microsoft Windows Vista 32 bit (SP1 or later) Microsoft Windows XP 32 bit (SP3 or later)			
Display Languages (*7)	English			

*1: When used in environments where temperature and humidity are over the values of 50°C 75%, 60°C 50%, 70°C 35%, and 80°C 25%, sensor hysteresis may fluctuate by values greater than ±1.5%RH. Under certain circumstances, it may take some time to return to normal measurement capability.
 *2: Compared to the value measured by the T&D standard sensor for calibration under our calibration light source.
 *3: Customers wishing to write their own software, please contact your local distributor for the serial communications protocol specifications. (Note: Optional serial communication cable TR-07C is also required.)
 *4: Battery life varies depending upon the ambient temperature in which it is used, the recording interval, the frequency of communication, and the battery performance. All estimates are based on operations carried out with a new battery and are in no way a guarantee of actual battery life. When infrared communication function is enabled, battery life may be shortened if the unit is used under the inverter type fluorescent lighting.
 *5: For installation, it is necessary to have Administrator (Computer Administrator) rights.
 *6: If you are using Windows 8, please note that our software is designed to be used in "Desktop" mode only.
 *7: We recommend using an operating system in the same language as the display language. Operation in different languages is not guaranteed.
 The specifications listed above are subject to change without notice.

Specifications

	TR-76Ui		TR-76Ui-H	
	THA-3001		HHA-3151 (High-Precision Type)	
Temperature/Humidity Sensor (External)	Thermistor	Polymer Resistance	Platinum Resistance	Electrostatic Capacitance
Measurement Channels	Temperature 1ch	Humidity 1ch	Temperature 1ch	Humidity 1ch
Measurement Units	°C, °F	%RH	°C, °F	%RH
Measurement Range (*1)	0 to 55 °C	10 to 95 %RH	-30 to 80 °C	0 to 99 %RH
Accuracy	±0.5 °C	±5 %RH [at 25 °C, 50 %RH]	±0.3°C [0 to 50 °C] ±0.5°C [all other temperatures]	±2.5 %RH [at 25 °C, 10 to 85 %RH] ±4.0 %RH [at 25 °C, 0 to 10 % or 85 to 99 %RH] At temperatures other than 25 °C and ≥ 0 °C, add ±0.1 %RH per degree of difference from 25. Humidity Hysteresis: ±1.5 %RH or lower (*)
Measurement Resolution	0.1 °C		0.1 °C	
Responsiveness	Response Time (90%): Approx. 7 min.		Response Time (90%): Approx. 7 min.	Response Time (90%): Approx. 20 sec.
CO2 Sensor (Internal)	NDIR			
Measurement Channels	CO2 Concentration 1ch			
Measurement Units	ppm			
Measurement Range	0 to 9,999 ppm			
Accuracy	±(50 ppm + 5 % of reading) [at 5,000 ppm or less] (*3)			
Measurement Resolution	Minimum of 1 ppm			
Responsiveness	Response Time (90%): Approx. 1 min.			
Logging Capacity	8,000 data sets (One data set consists of readings for all channels in that type of unit.)			
Recording Interval	Select from 15 choices: 1, 2, 5, 10, 15, 20, 30 sec. or 1, 2, 5, 10, 15, 20, 30, 60 min.			
Recording Mode	Endless (Overwrite oldest data when capacity is full) or One Time (Stop recording when capacity is full)			
LCD Display Items	Measurements, Battery Level, etc. - Measurements: CO2 concentration, Temperature or Humidity (fixed or alternating display)			
Communication Interfaces	USB Communication, Serial Communication (RS-232C) (*4), Infrared Communication (IrPHY 1.2 low power) (*5)			
External Alarm Terminal (*6)	Output Terminal: Open Drain Output (Voltage when OFF: DC less than 30V / Current when ON: less than 0.1A / Resistance when ON: about 15Ω)			
Power	AC Adaptor (AD-0638 or AD-0638-C), AA Alkaline Battery (LR6) x 4			
Battery Life	Approx. 2 days (batteries only without AC adaptor) (*7)			
Dimensions	H 96 mm x W 66 mm x D 46 mm (excluding protrusions and sensor)			
Weight	214 g (including batteries, excluding sensor)			
Operating Environment	Temperature: 0 to 45 °C, Humidity: 90 %RH or less (no condensation)			
Accessories	AA Alkaline Battery (LR6) x 4, AC Adaptor (AD-0638 or AD-0638-C), USB Communication Cable (US-15C), Temperature/Humidity Sensor (THA-3001 or HHA-3151), Software (CD-ROM), User's Manual Set (Warranty Included)			
Software Compatible OS (*8)	Microsoft Windows 8 32/64 bit (*9) Microsoft Windows 7 32/64 bit Microsoft Windows Vista 32 bit (SP1 or later) Microsoft Windows XP 32 bit (SP1 or later)			
Display Languages (*10)	English			

*1: Make sure to use the data logger within the operating environment as listed in the specifications.
 *2: When used in environments where temperature and humidity are over the values of 50°C 75%, 60°C 50%, 70°C 35%, and 80°C 25%, sensor hysteresis may fluctuate by values greater than ±1.5%RH. Under certain circumstances, it may take some time to return to normal measurement capability.
 *3: Stated value is the measurement accuracy of the CO2 sensor when Auto Calibration is operating properly. A change in atmospheric pressure directly influences the reading of CO2, which can cause measurement errors; a decrease in pressure by 10hPa results in a relative decrease in CO2 by 1.8%. In such a case, we recommend carrying out the Atmospheric Pressure Correction function found in CO2 Recorder for Windows.
 *4: Customers wishing to write their own software, please contact your local distributor for the serial communications protocol specifications. (Note: Optional serial communication cable TR-07C is also required.)
 *5: If you wish to use infrared communication to download recorded data, it is necessary to purchase the Data Collector TR-57DCI (sold separately).
 *6: In order to use the external alarm terminal, please prepare a compatible connector: JST PAP-04V-S.
 *7: Battery life varies depending upon the ambient temperature in which it is used, the recording interval, the frequency of communication, and the battery performance. All estimates are based on operations carried out with a new battery and are in no way a guarantee of actual battery life. Battery life may be shortened if the unit is used under inverter type fluorescent lighting.
 *8: For installation, it is necessary to have Administrator (Computer Administrator) rights.
 *9: If you are using Windows 8, please note that our software is designed to be used in Desktop mode only.
 *10: We recommend using an operating system in the same language as the display language. Operation in different languages is not guaranteed.
 The specifications listed above are subject to change without notice.