

[1]Product Appearance



*BM301 series


<Applications>

Design with excellent practicality and can be adapted to the various places like:

- . Hotels
- . Conference / Meeting rooms
- . Factories & Offices
- . Commercial Purposes
- . Residential / Institution Buildings

<Features>

- . Long life, up to 30,000 + hours
- . Light viewing angle of over 110°
- . Electricity consumption reduced 50%
- . Easy installation and low maintenance fee
- . Green product. Free of mercury and hazardous materials



[2]Specification

Model	BM301		BM201		BM18	
						
Power consumption (W/AC)	10W ±1W	14W ±1W	8W ±1W	12W ±1W	9W ±1W	16W ±1W
Cutout size	Ø125mm.	Ø165mm.	105x105mm	130x130mm	130x130mm	160x160mm
Luminous Flux(lm)	800lm	1120lm	640lm	960lm	810lm	1440lm
Input Voltage(V)	AC85 - 265V 50/60Hz					
Color Temperature(K)	3000K - 3500K, 6000K - 6500K					
Fixture Material	Aluminum & Acrylic IP40					
Life Span(hr) Deacay<70%	30,000					
Warranty	2 Years					

Work condition :

Temperature : 5°C~35°C Humidity : Below 85%

Do not use at high humidity or wet place.

Okumura & Systems Co.,Ltd.