

[1]Product Appearance



*USH-PL6060



*USH-PL30120

<Applications>

Design with excellent practicality and can be adapted to the various places like:
Office ceiling · shop · showroom · super market

<Features>

- Long life, up to 40,000 + hours
- Light viewing angle of over 120°
- Electricity consumption reduced 60%
- Easy installation and low maintenance fee
- Green product. Free of mercury and hazardous materials

[2]Specification

Model	USH-PL6060	USH-PL30120
Power consumption (W/AC)	45W ± 5%	
Input Voltage(V)	AC100V - 240V(NON-DIM) / AC 200V-240V(DIM) 50-60HZ(NON-DIM) / 50HZ (DIM)	
Luminous Flux(lm)	>2562lm (6000K) (high 2m. 296lx.)	>2642lm (6000K) (high 2m. 305lx.)
Color Temperature(K)	2700/5500K	
Dimmable	available	available
Size · Weight	595 mm (L) x 595 mm (W) x 11mm (H)	1195 mm (L) x 295 mm (W) x 11mm (H)
Fixture Material	PC/AL	
Life Span(hr) Deacay<70%	40,000	
Warranty	2 Years	

Work condition :

Temperature : 5°C~35°C Humidity : Below 85%

Do not use at high humidity or wet place.

Okumura & Systems Co.,Ltd.